

# Backhoe(LW)



The LW series backhoe is a strong design, it is used for ditching in farms and grazing lands, digging pool, cleaning water ways as well as assistant excavating work in construction and building roads.

Hydraulic transmission is used, featured with compact structure, flexibility. Convenient operation and quick mounting and dismounting. It uses hydraulic oil commonly with tractor. The hydraulic elements are standardized, convenient for operation and service.

To better accomplish different kinds of work, buckets of different sizes can be selected and mounted on it.

MODEL	LW-6	LW-7	LW-8
Suited to	25-35hp	30-50hp	55-80hp
3-point Linkage	Cat 1	Cat 1	Cat 1 or Cat 2
Working length	3167mm	3545mm	4209mm
Digging depth	2239mm	2277mm	2991mm
Extend height	3184mm	3171mm	4170mm
Unload height	1951mm	2104mm	2920mm
Leg spread	1800mm	2000mm	2000mm
Weight	494kg	555kg	650kg
Swing angle(boom)	140 degrees	140 degrees	140 degrees
Bucket width	250mm	300mm	400mm
FCA Price	USD1468	USD1673	USD1819

**1.Above models offered are with standard Chinese control valve, JIC standard fitting, comfortable seat with belt for safety,**

- 2. 9" bucket      USD75
- 3. 12" bucket    USD80
- 4. 15" bucket    USD95
- 5. 18" bucket    USD105
- 6. Reservoir tank with filter+gear box with Chinese hydraulic pump    USD150

Pls choose the buckets(9", 12", 15", 18") what you need for your backhoe,  
Pls tell me the port near to your address, and then I will calculate the freight cost for you!

Our warranty is one year, if there are any problem withtin one year,we will supply the warranty for you

The packing is iron frame, package size is 2.2\*0.8\*1m/unit

