



JINMA 164Y/204Y



Smart/Updated E-mark/Garden model



Model	164Y		204Y	
	Four wheel drive		Four wheel drive	
Overall Dimensions L×W×H(mm)	2080×1150×2110		2080×1150×2110	
Wheel Track (mm)	Front		Rear	
	750		800	
Wheel Base(mm)	1350		1350	
Ground Clearance (mm)	200		200	
Rated Traction Force(N)	3.5		3.6	
Construction Mass(kg)	837		837	
Min Turning Radius(mm)	10.1		10.1	
Theoretical Speed	Low gear		High gear	
	11		11	
	11.1		11.1	
	11.1		11.1	
	11.1		11.1	
	11.1		11.1	
Engine Specifications	Model		164Y	
	Type		In-line - water cooled, 4 stroke cycle	
	Rated Power(kw/hp)		11.4/15	
	Rated Speed (rpm)		2300	
	Bore×Stroke (mm)		75×75.6	
	Total Displacement(L)		1.629	
Drive System	Clutch		7 inch single clutch	
	Gear Box		(11)×2	
	Main Drive		split bevel gear	
	Differential		Two bevel gears	
	Differential Lock		Jaw lock	
	Final Transmission		Single stage planetary gear	
Traveling Mechanism	Type		Front	
	Steering Gear		Rear	
Working Device	Hydraulic System		Lifting Capacity at 610mm Behind Lift Point (N)	
	P.T.O Shaft		3-Point Suspension	
	Rotating Speed (rpm)		540/1000	
	Spline Size		1 spline shaft	
	Options		Turf tyre 8.0-12/110, 9-16	

JINMA 254E



Updated E-mark/Easy operation



Model	254E	
	Four wheel drive	
Overall Dimensions L×W×H(mm)	3300×1500×1650	
Wheel Track (mm)	Front	
	1050	
Wheel Base(mm)	Rear	
	1200	
Ground Clearance (mm)	175	
Rated Traction Force(N)	320	
Construction Mass(kg)	1527	
Min Turning Radius(m)	3	
Theoretical Speed (km/h)	Forward	
	1.77/2.10/4.23/5.83/8.16/12.46/18.66/26.96	
Theoretical Speed (With crawler) km/h	Reverse	
	2.33/11.25	
Theoretical Speed (With crawler) km/h	Forward	
	0.33/0.50/0.79/1.09/1.53/2.32/3.65/5.83	
Theoretical Speed (With crawler) km/h	Reverse	
	0.43/2.10	
Model	254E	
	Type	
	In-line - water cooled, 4 stroke cycle	
	Rated Power(kw/hp)	
	18.4/25	
	Rated Speed (rpm)	
	2400	
Bore×Stroke (mm)	90×95	
	Total Displacement(L)	
	2.453	
	Clutch	
	9 inch dual clutch	
	Gear Box	
	(11)×2	
Main Drive	Two bevel gears	
	Differential	
	Two planetary gears	
	Differential Lock	
	Jaw lock	
	Final Transmission	
	Single gear gear	
Type	Front	
	Rear	
Steering Gear	Hydraulic steering	
	Disc brake	
Hydraulic System	Lifting Capacity at 610mm Behind Lift Point (N)	
	3-Point Suspension	
	Category :I	
	Rotating Speed (rpm)	
	540/1000	
	Spline Size	
	34, 79	
P.T.O Shaft	Turf tyre 26x7.5-12/11, 2-20	

JINMA 454E



Updated E-mark/Low fuel consumption



	Model	454E
	Drive Type	Four wheel drive
	Overall Dimensions L×W×H(mm)	3275×1500×2100
Wheel Track (mm)	Front	1050
	Rear	1200
	Wheel Base(mm)	1855
	Ground Clearance (mm)	250
	Rated Traction Force(N)	7500
	Construction Mass(kg)	1597
	Min Turning Radius(m)	3.5
Theoretical Speed (km/h)	Forward	1.86/2.34/4.67/6.45/9.02/12.70/18.28/26.97
	Reverse	2.45/11.84
Theoretical Speed (With crawler) km/h	Forward	0.35/0.50/0.79/1.09/1.53/2.32/3.65/5.83
	Reverse	0.46/2.11
	Model	454E
	Type	In-line - water cooled, 4 stroke cycle
	Rated Power(kw/hp)	25.1/35
	Rated Speed (rpm)	2400
	Bore×Stroke (mm)	90×95
	Total Displacement(L)	2.453
	Clutch	10 inch dual clutch
	Gear Box	(11)×2
	Main Drive	Two bevel gears
	Differential	Two planetary gears
	Differential Lock	Jaw lock
	Final Transmission	Single gear gear
Type	Front	6.00-16
	Rear	11-21
Steering Gear	Hydraulic steering	
	Brake	Disc brake
Hydraulic System	Lifting Capacity at 610mm Behind Lift Point (N)	7300
	3-Point Suspension	Category :I
	Rotating Speed (rpm)	540/1000
	Spline Size	34, 79
P.T.O Shaft	Turf tyre 26x7.5-12/11, 2-20	



Huanghai Jinma brand
CHINA WELL-KNOWN BRAND



Slasher



Rotary Tiller



Front End loader & Backhoe



4 in 1 Front End loader



SnowBlower

