

Weifang Kai Ruite Agricultural Machinery Co.,Ltd.

Sadin industry zone,south of Beihai Road,Weifang,Shandong,CHINA262100

Email: bohengli@wffortune. com WhatsApp: +86 15689178222

Quotation

Model	SD804-TB
Engine	LAIDONG DIESEL ENGINE (Emissions:Chinese Standard III)
Tire	8.3-24/14.9-30
Basic Configuration	two stage clutch,12F+12R shuttle shift,Hydraulic steering,duel speed PTO(540/760 r/min),side shift, Shock absorbing seat, Maintenance free battery, flat floor ,sectional type rear power takeoff shaft , streamlining metal hood,four wheels drive.
Basic quotation	USD10620/set FOB QINGDAO,CHINA
Optional	
ROPS	USD129.
Sunshade	USD95.
Cabbin with fan	USD1048.
Cabbin with Heater	USD1129.
Cabbin with A/C	USD1451.
16F+8R creeper shift	USD161.
Swing drawbar	USD50.
2-way valve	USD225.
1-way valve	USD113.
Air brake	USD129.
Tyre(8.3-20/12.4-28)(4WD)	-USD241.
Front ballast	USD80.
Rear ballast	USD95
Power lift and fall	USD193.
Packing by double iron frame	USD241. (6SETS/40'HQ)

Technical Parameters

Rated Engine Power(Kw)	58.8	Wheel base(mm)	2072
Drive type	4x4 (4wd)	Shifts	12+12
Length(mm)	3900	Max.traction(4wd)(KN)	16.5
Width(mm)	1795	Forward speed range(Km/h)	2.46-32.73
Height(mm)	2510	Reverse speed(Km/h)	2.15-28.69
Tread of front wheel(mm)	1450-1550	PTO(r/min.)	540/760 optional 760/850, 540/1000,760/1000
Tread of rear wheel(mm)	1300-1500		





SD804A (70-90 马力) 欧马赫系列拖拉机

SD804A(70-90hp) Series Aumahr Tractor

产品特点：

经济实用，效率高

- 配套名优发动机，扭矩储备大、动力强劲。
- 动力排放升级、档位分布合理，农艺适应性强，拥有各种农田作业、运输作业等所需的理想工作速度，作业效率更高，燃油经济性更好，技术更先进。

安全稳妥，可靠性强

- 加强型前驱动桥，水田适应性更强，可靠性强。
- 采用新型力位调节提升器，操纵、调节更灵活。
- 双作用离合器，轻便、可靠。
- 加强型传动系，传动效率高，可靠性强。
- 12+12 模式换挡，速度匹配合理，作业效率高，适应性强。
- 动力输出分段，维护更方便。

人性化设计，驾驶更轻松

- 整车人机工程优化设计，增强驾驶员的安全性、舒适性。
- 动力输出转速可选择 540/760 转 / 分等多种转速，可配套多种农机具，适应范围更广。

CHARACTERISTICS:

- Famous brand four-cylinder direct injection diesel engines with sound fuel efficiency and high torque output.
- Center console with simple structure, high cost efficiency and easy maintenance; side console for driving and riding comfort.
- Optional single/double-acting clutches for different needs and operation; special ceramic material for friction plates with high reliability as well as low use and maintenance cost.
- Brand-new 12F+12R shuttle-type gear shifting with quick forward and reverse gear shifting; 8F+4R gears for multi-function operation.
- Farmland tires, grass tires, engineering tires and many other tires to meet needs of different working conditions.

技术参数 / TECHNICAL PARAMETERS:

发动机功率 (千瓦) / Rated Engine Power(Kw)	58.8	轴距 (毫米) / Wheel Base(mm)	2050
驱动形式 / Driven Type	4×4 轮式 4WD	档位 / Shifts	12+12
长 (毫米) / Length (mm)	4050	最大牵引力 (四轮驱动) (千牛) / Max.Traction (4WD)(KN)	16.5
宽 (毫米) / Width (mm)	1820	前进速度范围 (千米 / 小时) / Forward Speed Range(Km/h)	2.46-32.73
高 (毫米) / Height (mm)	2610	倒退速度范围 (千米 / 小时) / Reverse Speed (Km/h)	2.15-28.69
前轮轮距 (毫米) / Tread of Front Wheel(mm)	1460(920、1040)	动力输出轴 (转 / 分) / PTO(Rev./min)	540/760
后轮轮距 (毫米) / Tread of Rear Wheel(mm)	1380 (1200、1300、1400、1500)		